


# Snap action contact pressure switch, field adjustable, metal fitting.

## 3 poles DT contact : Type MN3

### DIMENSIONS



**Uses:** High electrical rating, for 250V.

**Main applications:** Pressure sensing on water heaters, boilers, spas and swimming pools heaters and filters, electrical appliances (For incorporation).

**Membrane:** EPDM, dia 45 mm. Silicone or NBR on request

**Fluid:** water or air

**Fitting:** Brass (stainless steel on request)

**Pressure:** positive

**Housing:** PA66, UL94 VO, IP00

**Contacts:** 3 SPDT switches, snap action. NO or NC contacts available with MOQ Electrical rating: Depends on micro-switch operating force that is linked to the electrical rating

- Standard rating micro-switch (medium and high pressure calibration only): 16A 125/250VAC; 1/2HP 125VAC; 3/4HP 250VAC

- High rating micro-switch (medium and high pressure calibration only): 2HP 240V, 21(8) A 240V (UL, CSA VDE switch)

- Low force micro-switch (set points less than 150 mbar): 1/4HP 6(1) A 240V (UL, CSA VDE switch)

- On request: up to 25A 250V

**Action:** momentary.

**Set point calibration:** Field adjustable with screw driver at +/- 20% of the factory calibration value


**Calibration limits:** 150 to 1500 mbar

**Electrical connection:** 6.35 x 0.8 mm terminals

**Maximum pressure:** 6 bars (87 PSI)

**Ambient temperature limits:** 0 to 85°C

### Available pressure inlet fittings ①



References ( SPDT contact, brass fitting, calibrated at 400 mbar ):

Pressure inlet	Standard rating micro- switch	Low pressure micro-switch	High rating micro-switch
1/8" NPT	MN30U145H040DE00	MN30U540H040DE00	MN30U647H040DE00
1/8" BSPT	MN30U145L040DE00	MN30U540L040DE00	MN30U647L040DE00
1/8" BSPP	MN30U145D040DE00	MN30U540D040DE00	MN30U647D040DE00
1/4" NPT	MN30U145K040DE00	MN30U540K040DE00	MN30U647K040DE00
1/4" BSPT	MN30U1452040DE00	MN30U5402040DE00	MN30U6472040DE00
1/4" BSPP	MN30U1453040DE00	MN30U5403040DE00	MN30U6473040DE00
Smooth spout dia 4 mm	MN30U145E040DE00	MN30U540E040DE00	MN30U647E040DE00
Spout dia 6 mm	MN30U145F040DE00	MN30U540F040DE00	MN30U647F040DE00
Fluted spout dia 6 mm	MN30U145G040DE00	MN30U540G040DE00	MN30U647G040DE00
Barbed spout dia 10 mm	MN30U145J040DE00	MN30U540J040DE00	MN30U647J040DE00

Other set point values: replace 040 in the product reference by the calibration value

