



# Sample and quotation request form

## Air switch or pressure switch



Company		Address	
Name and title		City	
Email		Post code	
Website		country	
Tel		Fax	

**1/ Description of pressure switch application :** (Air switches : must give connection tube diameter and remote control distance)  
 .....

<b>2/ Pressure characteristics</b>		
<b>2A/ Fluid to be controlled:</b> <input type="checkbox"/> air, <input checked="" type="checkbox"/> water, <input type="checkbox"/> gas, <input type="checkbox"/> ozone, <input type="checkbox"/> other : specify	<b>2B/ Maximum peak Pressure</b> Value: 0.8MPa Unit: <input type="checkbox"/> mbars , <input type="checkbox"/> Kpa, <input type="checkbox"/> PSI, <input type="checkbox"/> Pa, <input type="checkbox"/> <input type="checkbox"/> Torr , <input type="checkbox"/> Inch of water <input type="checkbox"/> other : .....	<b>2C/ Calibration pressure</b> Value: ..... Tolerance: ..... Unit: <input type="checkbox"/> mbars , <input type="checkbox"/> Kpa, <input type="checkbox"/> PSI, <input type="checkbox"/> Pa, <input type="checkbox"/> Torr , <input type="checkbox"/> Inch of water <input type="checkbox"/> other : .....
<b>2D/Pressure connection type</b> <input type="checkbox"/> spout OD:..... <input type="checkbox"/> quick connect, OD:..... <input type="checkbox"/> barbed OD :..... <input checked="" type="checkbox"/> Threaded:G1/2".. (specify Metric, NPT, BSP or other)	<b>2E / Pressure connection material</b> <input checked="" type="checkbox"/> Brass, or <input checked="" type="checkbox"/> PA66 <input type="checkbox"/> Stainless steel <input type="checkbox"/> 304 <input type="checkbox"/> 316 <input type="checkbox"/> ABS <input type="checkbox"/> PBT <input type="checkbox"/> other : specify	<b>2F/ Differential value</b> (Pressure difference between contacts open and close when pressure changes) <input checked="" type="checkbox"/> no specific request <input type="checkbox"/> 5% of calibration value <input type="checkbox"/> 10% of calibration value <input type="checkbox"/> other :.....

<b>3/ Electrical characteristics</b>			
<b>3A/Tension type</b> <input checked="" type="checkbox"/> AC or <input checked="" type="checkbox"/> DC	<b>3B/Voltage</b> <input type="checkbox"/> 400V <input type="checkbox"/> 240V <input checked="" type="checkbox"/> 220V(ac) <input type="checkbox"/> 110V <input checked="" type="checkbox"/> 24V(dc) <input type="checkbox"/> 5V <input type="checkbox"/> <5V Other :	<b>3C/ Amperage</b> <input type="checkbox"/> <10mA <input checked="" type="checkbox"/> 10mA-100Ma(24Vdc) <input type="checkbox"/> 100mA-1A <input type="checkbox"/> 1A-6A <input type="checkbox"/> 6A-10A <input type="checkbox"/> 10A-16A <input type="checkbox"/> 16A-22A <input checked="" type="checkbox"/> 22- 25A(220Vac)	<b>3D/ Load</b> <input type="checkbox"/> motor, <input checked="" type="checkbox"/> resistive, (220Vdc) <input type="checkbox"/> thermocouple, <input checked="" type="checkbox"/> computer circuit (24Vdc) <input type="checkbox"/> electronic circuit <input type="checkbox"/> other : ..... .....
<b>3E/ Approvals</b> <input type="checkbox"/> Not requested <input type="checkbox"/> UL <input type="checkbox"/> CSA <input type="checkbox"/> VDE, <input type="checkbox"/> ENEC <input checked="" type="checkbox"/> CCC <input type="checkbox"/> JIS <input type="checkbox"/> CE <input type="checkbox"/> Other :	<b>3F/Electrical life</b> <input type="checkbox"/> 100 cycles <input type="checkbox"/> 1000 cycles <input type="checkbox"/> 3000 cycles(220Vdc) <input checked="" type="checkbox"/> 10000 cycles(24Vdc) <input type="checkbox"/> 50000 cycles <input type="checkbox"/> 100000 cycles <input type="checkbox"/> other	<b>3G/ Contact type :</b> <input type="checkbox"/> <b>nc</b> :contact opens by pressure rise) <input checked="" type="checkbox"/> <b>no</b> :contact closes by pressure rise), <input type="checkbox"/> <b>dt</b> :change over contact)	
<b>3H/ Number of switches</b> <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3	<b>3I/ Electrical Terminals</b> <input type="checkbox"/> screw <input type="checkbox"/> ¼ QC (6.3 x 0.8 mm) <input checked="" type="checkbox"/> 4.8 x 0.8 mm	<b>3J/ Contact action :</b> <input checked="" type="checkbox"/> Automatic reset (momentary) <input type="checkbox"/> Manual reset <input type="checkbox"/> Latching (Bistable)	

**4/ Adjustment characteristics**  
 Factory set and sealed  
 Field access Screw adjustment  Visual scale adjustment. Specify adjustment range : ... ;

<b>5/ Environmental conditions</b>		
<b>5/A Ambient Temperature</b> Mini 0°C.....°F Maxi 45°C..... °F	<b>5/B Fluid temperature:</b> Mini 4°C.....°F Maxi 90°C..... °F	<b>5/C Protection</b> <input checked="" type="checkbox"/> No protection <input type="checkbox"/> Dustproof <input type="checkbox"/> Waterproof (if manual reset, specify internal <input type="checkbox"/> or external manual reset <input type="checkbox"/>

**6/ Accessories to be supplied with product**  
 Plastic nut  Brass nut  Stainless steel nut  Tube retaining nut  Gasket  other 明:

**7/ Requirements**  
 Samples. Requested samples quantity :  1  2  other :4...  
 Quotation. Annual use: 100000 Ordering quantity:.....Shipping quantity: .....  
 Final destination country

Date: 2004.10.13.

1、DC24V type quantity is: 90000, AC220V type quantity is 10000.

2、G1/2 G3/8.