



ULTIMHEAT®

Sample and quotation request form In line heaters



Date	Customer, Contact name, Email address	Project name or customer reference	EAU (Estimated annual use)
------	---------------------------------------	------------------------------------	----------------------------

To fill this form, you must refer for compatibility to the Ultimheat in line heaters catalog, section 2, P16 to 22

Tube diameter: <input type="checkbox"/> Dia 25.4 (P17) <input type="checkbox"/> Dia 38.1 (P18) <input type="checkbox"/> Dia 48.3 (P19) <input type="checkbox"/> Dia 57.3 (P20) <input type="checkbox"/> Dia 76.2 (P21)							
Heating element options: <input type="checkbox"/> HE1 <input type="checkbox"/> HE2 <input type="checkbox"/> HE13 <input type="checkbox"/> HE14 <input type="checkbox"/> HE25 <input type="checkbox"/> HE26 <input type="checkbox"/> HE29 <input type="checkbox"/> HE30 <input type="checkbox"/> HE34 <input type="checkbox"/> HE40 <input type="checkbox"/> HE41 <input type="checkbox"/> HE50 <input type="checkbox"/> HE95							
Heating element voltage : <input type="checkbox"/> 110 VAC <input type="checkbox"/> 220 VAC <input type="checkbox"/> 230 VAC <input type="checkbox"/> 240 VAC <input type="checkbox"/> 380 VAC <input type="checkbox"/> 400 VAC <input type="checkbox"/> Other	Electrical supply: <input type="checkbox"/> Single phase <input type="checkbox"/> 3 phases <input type="checkbox"/> 3 phases + neutral <input type="checkbox"/> 110 VAC <input type="checkbox"/> 220 VAC <input type="checkbox"/> 230 VAC <input type="checkbox"/> 240 VAC <input type="checkbox"/> 380 VAC <input type="checkbox"/> 400 VAC <input type="checkbox"/> Other:	Heating element material: (not for HE50) <input type="checkbox"/> 304 <input type="checkbox"/> 304L <input type="checkbox"/> 316 <input type="checkbox"/> 316L <input type="checkbox"/> 321 <input type="checkbox"/> Incolloy 800 <input type="checkbox"/> Other:	Heating element length:mm Cold zone length : <input type="checkbox"/> 60 mm (standard) <input type="checkbox"/> other: mm	Heating elements qty: <input type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3	Power of each heating element:W Total power:W	Watt density (W/cm²): <input type="checkbox"/> 2 <input type="checkbox"/> 5 <input type="checkbox"/> 8 <input type="checkbox"/> 10 <input type="checkbox"/> 15 <input type="checkbox"/> 20 <input type="checkbox"/> Other:	Pocket options: <input type="checkbox"/> no <input type="checkbox"/> PC1 <input type="checkbox"/> PC4 <input type="checkbox"/> PC2 <input type="checkbox"/> PC3 <input type="checkbox"/> PC5 <input type="checkbox"/> PC6 <input type="checkbox"/> PC7 <input type="checkbox"/> PC8 Length D:mm

Electrical housing model and equipment options

Size and catalog page	Enclosure with controls options	Enclosures without controls	Specify cable gland position, model and cable diameter
Catalog P.17, Dia 25.4 mm	<input type="checkbox"/> IL1 <input type="checkbox"/> IL2 <input type="checkbox"/> IL3 <input type="checkbox"/> IL4 <input type="checkbox"/> IL5 <input type="checkbox"/> IL6	<input type="checkbox"/> IL0 <input type="checkbox"/> S1 <input type="checkbox"/> S2 <input type="checkbox"/> S3 <input type="checkbox"/> S18	
Catalog P.18, Dia 38.1 mm	<input type="checkbox"/> IM7 <input type="checkbox"/> IM8 <input type="checkbox"/> IM9 <input type="checkbox"/> IM10	<input type="checkbox"/> IM0 <input type="checkbox"/> S1 <input type="checkbox"/> S2 <input type="checkbox"/> S3 <input type="checkbox"/> S18	
Catalog P. 19, Dia 48.3 mm	<input type="checkbox"/> IN1 <input type="checkbox"/> IN2 <input type="checkbox"/> IN3 <input type="checkbox"/> IN4 <input type="checkbox"/> IN5 <input type="checkbox"/> IN6 <input type="checkbox"/> IN7	<input type="checkbox"/> S3 <input type="checkbox"/> S12 <input type="checkbox"/> S13 <input type="checkbox"/> S14	
Catalog P.20, Dia 57.3 mm	<input type="checkbox"/> IP1 <input type="checkbox"/> IP2 <input type="checkbox"/> IP3 <input type="checkbox"/> IP4 <input type="checkbox"/> IP5 <input type="checkbox"/> IP6 <input type="checkbox"/> IP7 <input type="checkbox"/> IP8 <input type="checkbox"/> IP9 <input type="checkbox"/> IP10	<input type="checkbox"/> S3 <input type="checkbox"/> S8 <input type="checkbox"/> S12 <input type="checkbox"/> S13 <input type="checkbox"/> S14	
Catalog P.21-22, Dia 76.2 mm	<input type="checkbox"/> IT1 <input type="checkbox"/> IT2 <input type="checkbox"/> IT3 <input type="checkbox"/> IT4 <input type="checkbox"/> IT5 <input type="checkbox"/> IT6 <input type="checkbox"/> IT7 <input type="checkbox"/> IT8 <input type="checkbox"/> IT9 <input type="checkbox"/> IT10 <input type="checkbox"/> IT11 <input type="checkbox"/> IT12 <input type="checkbox"/> IT13	<input type="checkbox"/> S5 <input type="checkbox"/> S6 <input type="checkbox"/> S8 <input type="checkbox"/> S12 <input type="checkbox"/> S13 <input type="checkbox"/> S14	

Fittings options

Main fittings options: <input type="checkbox"/> F1 <input type="checkbox"/> F2 <input type="checkbox"/> F3 <input type="checkbox"/> F4 <input type="checkbox"/> F5 <input type="checkbox"/> F6 <input type="checkbox"/> F7 <input type="checkbox"/> F8 <input type="checkbox"/> F9 <input type="checkbox"/> F10 <input type="checkbox"/> F11 <input type="checkbox"/> F12 <input type="checkbox"/> F13 <input type="checkbox"/> F14 <input type="checkbox"/> F15 <input type="checkbox"/> F16 <input type="checkbox"/> F17 <input type="checkbox"/> F18 <input type="checkbox"/> F19 Auxiliary fittings options: <input type="checkbox"/> A1 <input type="checkbox"/> A2 <input type="checkbox"/> A3 <input type="checkbox"/> A4 <input type="checkbox"/> A5 <input type="checkbox"/> A6 <input type="checkbox"/> A7 <input type="checkbox"/> A8 <input type="checkbox"/> A9 <input type="checkbox"/> A10 <input type="checkbox"/> A11 <input type="checkbox"/> A12 <input type="checkbox"/> A13 <input type="checkbox"/> A14 <input type="checkbox"/> A15 <input type="checkbox"/> A16 <input type="checkbox"/> A17 <input type="checkbox"/> A18 <input type="checkbox"/> A19 <input type="checkbox"/> A20 Fitting and tube material: <input type="checkbox"/> Brass <input type="checkbox"/> 304 <input type="checkbox"/> 304L <input type="checkbox"/> 316 <input type="checkbox"/> 316L <input type="checkbox"/> Other:.....

Pipe and other various options

Pipe input output position <input type="checkbox"/> MT1 <input type="checkbox"/> MT2 <input type="checkbox"/> MT4 Angle :° <input type="checkbox"/> MT5 <input type="checkbox"/> MT6 <input type="checkbox"/> MT7	Pipe forming <input type="checkbox"/> PF1 A= B=..... <input type="checkbox"/> PF2 A= B=..... C=..... <input type="checkbox"/> PF3 <input type="checkbox"/> PF4 <input type="checkbox"/> PF5 <input type="checkbox"/> PF6 <input type="checkbox"/> PF7 <input type="checkbox"/> PF8 <input type="checkbox"/> PF9 <input type="checkbox"/> PF10 <input type="checkbox"/> PF11 <input type="checkbox"/> PF12 lengthmm <input type="checkbox"/> PF13 <input type="checkbox"/> PF14 <input type="checkbox"/> CP1 length: mm	Grounding terminals and brackets <input type="checkbox"/> GT5 <input type="checkbox"/> GT6 <input type="checkbox"/> GT7 <input type="checkbox"/> GT8 <input type="checkbox"/> GT9-1 <input type="checkbox"/> GT9-2 <input type="checkbox"/> GT9-3	Electrical options: <input type="checkbox"/> UA 38 <input type="checkbox"/> UA 40 UL <input type="checkbox"/> UA 40 CE Cable length: mm <input type="checkbox"/> UA 18	Thermostats/TCO options, if not included in main models with controls <input type="checkbox"/> ST1 <input type="checkbox"/> ST2 <input type="checkbox"/> ST3 <input type="checkbox"/> ST4 <input type="checkbox"/> ST5 <input type="checkbox"/> ST6 <input type="checkbox"/> ST11 <input type="checkbox"/> ST12 <input type="checkbox"/> ST13	Pressure switch option, if not included in main models with controls <input type="checkbox"/> SP1 <input type="checkbox"/> SP2 <input type="checkbox"/> SP3 <input type="checkbox"/> SP5
--	--	---	--	---	---

Thermostats calibration

If product includes disc thermostat, specify temperatures : open:°C ±°C close:°C ±°C (or manual reset)	If product includes control bulb and capillary thermostat, specify temperature range: From °C To °C	If product includes manual reset bulb and capillary thermostat, specify set point value:°C ± ...°C	If product includes thermal fuse , specify set point value:°C
---	---	--	---

Attention: all combinations are not possible!
 NB: many more combinations and housings are available. If you do find exactly what you want in this document, , please describe or make a sketc hereunder: